

Amador

KEY FEATURES

- Intel® Celeron® N2807 1.58GHz (Up to 2.16GHz)
- 2GB DDR3 Memory
- Windows® Embedded POS Ready 7
- Resistive Touch
- Fan Free
- Gigabit LAN
- VESA Mount Capability
- Multiple Height Adjustments
- Low-Profile, Foldable Base
- Options
 - Biometric Fingerprint/Encryption-Capable MSR, Rear Display, Printer, Cash Drawer



About Posiflex

- Designer and manufacturer of Point-of-Service and industrial touch terminals
- Revolutionary technology, reliable quality, reasonable pricing and recognized service
- Delivers reliable terminals for maximum uptime and lower total cost of ownership
- Comprehensive suite of peripherals and services
- Innovative excellence since 1984 with more than 30 patents for innovation
- Global presence
- Two ISO 9001/9002/14001 Certified Facilities

Outstanding Price/Performance

Amador offers reliability which was designed, engineered and purpose built for quality - but at a very competitive price for outstanding price / performance.

Amador includes Windows Embedded POS Ready 7 with 2GB of memory running on an Intel Celeron CPU. Amador supports a full range of peripherals like encryption-capable MSR with fingerprint, rear mount customer pole display, cash drawers and printers and more. The low-profile base is sleek and fully foldable, creating optimal viewing for ease of use. Amador's use of an Intel embedded CPU and an embedded Windows operating system, unlike similarly priced terminals using consumer grade components, assures long term support for extended rollouts and ease of servicing.

System Specifications	Amador
Processor	Intel® Celeron® N2807 1.58GHz (Up to 2.16GHz) 1MB Smart Cache
System Memory	2GB DDR3L 1333MHz
Display	15" LED-Backlit LCD Panel (1024 x 768)
Touch	Resistive 5-Wire
Communications	Gigabit LAN
Storage	320GB HDD
Passive Cooling	Yes
Operating Systems	Windows Embedded POS Ready 7

Physical Dimensions	
Dimensions (WxDxH)	14.6" x 12.5" x 9.9"
Weight (lbs)	11.0

Connectivity	
COM Port(s)	3 x DB9 Serial 1 x RJ-50 Serial
CR Port	1 Port (Controls 2 Drawers) Dual Independent Open Sensor COM1/COM5 Select
USB 2.0 Port(s)	4 on I/O Panel 1 on Rear I/O
Parallel Port	1, via Optional Conversion Cable
Display Port	1 VGA Port
VESA Mountable	Yes

Environmental	
Operating Conditions	0°C - 40°C, 20% - 90% Relative Humidity
Storage Conditions	-20°C - 70°C, 10% - 90% Relative Humidity

Peripherals	
SA100	Magnetic Stripe Reader (Encryption Capable)
SA300	Magnetic Stripe Reader (Encryption Capable, Optional Biometrics)
PD2609UE0017A	Rear Display
LM3010	Secondary Monitor
PP9000	Thermal Printer (80mm wide, printing speed: 300mm/second)
CR3100	Cash Drawer
CR6300	Cash Drawer (printer driven and USB options available)

Available Services

- **Standard and Extended Warranty**
Extend your depot warranty up to 5 years.
- **Advance Exchange**
We ship overnight replacement equipment directly to your business. You return the faulty unit to Posiflex.
- **OnSite Service**
Expert technicians will efficiently handle the complete equipment swap and return process.
- **Regional Repair Depots**
Three regional depots assure fast turn-around time on repairs.
- **Post Warranty Support**
Spare parts, in addition to a flat rate repair program, for post warranty needs.
- **Installation Services**
Let our nationwide network of experts stage and install your equipment.
- **OEM Design and Integration**
Our Product Development Team helps design equipment, for custom hardware applications.



Posiflex designs, engineers and manufactures:

Touch Screen Terminals | **Printers** | **Magnetic Stripe Readers** | **Cash Drawers** | **Rear/Pole Displays**

POSIFLEX™

Posiflex Business Machines, Inc.
30689 Huntwood Ave.
Hayward, CA 94544

P: 888-968-1668

F: 510-475-0982

sales.department@posiflexusa.com

www.posiflexusa.com